

AXIS Camera Station S2208 Appliance

All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2208 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2208 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 8 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2208 provides a reliable surveillance solution.

- > All-in-one solution with integrated PoE switch
- > High-definition surveillance with up to 4K resolution
- > AXIS Camera Station licenses included
- > Full compatibility with Axis products



www.cxis.com T10136416/EN/M9.2/2201

	AXIS Camera Stati	on S2208	Appliance
Licenses	8 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).		Up to 8 cameras split view Supports two monitors, maximum one 4K monitor recommended Playback: Supports the same split scenarios as live view Supports only one monitor
System scalability	Qualified for up to 8 video channels and 16 doors		
Hardware		Recording	Qualified for recording up to 8 video channels with a total recording rate up to 192 Mbit per second
Processor	Intel® Core™ i3		recording rate up to 192 Mort per second
Memory	8 GB	General	M:
Storage	Surveillance Class HDD Total HDD slot: 2	Operating system	n Microsoft® Windows® 10 IoT Enterprise SAC Operating system recovery: yes Operating system drive: 120 GB SSD
C 11 1	Free HDD slot: 1 Out-of-the-box storage: 4 TB (1x4 TB)	Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity: 10–90% RH (non-condensing)
Switch	8 ports integrated, 135 W total power budget Power over Ethernet (PoE) IEEE 802.3at Class 4	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Graphic card	Intel® HD Graphics	Approvals	EMC
Power	Max 270 W, 135 W PoE dedicated 100 - 240 V AC, 3.5 A, 50/60 Hz 54 V DC, 5 A External power adapter	, 44, 614.5	CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A
Connectors	Front side: 1x USB 3.0 1x Audio line in 1x Audio line out Rear side Switch: 8x PoE ports 10/100 Mbps 1x SFP 10/100/1000 Mbps 1x RJ45 10/100/1000 Mbps Rear side Server: 1x RJ45 10/100/1000 Mbps 2x USB 2.0 1 Displayport™ 1 HDMI port		Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1, IS 13252
		Dimensions	330 x 230 x 78 mm (13 x 9.1 x 3.1 in)
		Weight	5.8 kg (12.8 lb)
		Included accessories	Rack ears, power adapter
		Optional accessories	Surveillance Hard Drive 4 TB available from Axis AXIS TS2901 Appliance Stand Axis desktop terminals Axis Ethernet surge protector For more accessories, see axis.com
Video		Warranty	Recorder and hard drive: 5-year warranty, see axis.com/warrant
Video streaming	Live view: 1 x 4K stream full screen	,	

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

4 split x 1080p

Environmental responsibility: axis.com/environmental-responsibility

