

AXIS Camera Station S2216 Appliance

All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2216 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2216 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 16 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2216 provides a reliable surveillance solution.

- > **All-in-one solution with integrated PoE switch**
- > **High-definition surveillance with up to 4K resolution**
- > **AXIS Camera Station licenses included**
- > **Full compatibility with Axis products**



AXIS Camera Station S2216 Appliance

Licenses	16 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	4 split x 1080p Up to 16 cameras split view Supports two monitors, maximum one 4K monitor recommended
System scalability	Qualified for up to 16 video channels and 32 doors	Playback: Supports the same split scenarios as live view Supports only one monitor
Hardware		
Processor	Intel® Core™ i5	
Memory	8 GB	
Storage	Surveillance Class HDD Total HDD slot: 4 Free HDD slot: 2 Out-of-the-box storage: 8 TB (2x4 TB)	
RAID	RAID levels: 0, 1, 10	
Switch	16 ports integrated, 260 W total power budget Power over Ethernet (PoE) IEEE 802.3at Class 4	
Graphic card	Intel® HD Graphics	
Power	Max 520 W, 260 W PoE dedicated 100 - 240 V AC, 6.5-2.5 A, 50/60 Hz	
Connectors	Front side: 1x USB 3.0 1x Audio line in 1x Audio line out Rear side Switch: 16x PoE ports 10/100 Mbps 1x SFP 10/100/1000 Mbps 1x RJ45 10/100/1000 Mbps Rear side Server: 1x RJ45 10/100/1000 Mbps 2x USB 2.0 1 Displayport™ 1 HDMI port	
Video		
Video streaming	Live view: 1 x 4K stream full screen	
Recording	Qualified for recording up to 16 video channels with a total recording rate up to 384 Mbit per second	
General		
Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Operating system recovery: yes Operating system drive: 120 GB SSD	
Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity: 10-90% RH (non-condensing)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)	
Approvals	EMC CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1, IS 13252	
Dimensions	476 x 440 x 45 mm (18.7 x 17.3 x 1.8 in), 1U chassis	
Weight	11 kg (24.3 lb)	
Included accessories	Rack rails, power cord	
Optional accessories	Surveillance Hard Drive 4 TB available from Axis Axis desktop terminals Axis Ethernet surge protector For more accessories, see axis.com	
Warranty	Recorder and hard drive: 5-year warranty, see axis.com/warranty	

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility