

AXIS Q6078-E PTZ Camera

Outdoor-ready PTZ with UHD 4K

AXIS Q6078-E PTZ Camera offers UHD 4K with 20x optical zoom for outstanding video quality. It offers great overviews and detail with the clearest, sharpest colors. This high-performance outdoor PTZ camera comes with autotracking 2 with click and track functionality, as well as an orientation aid for active object tracking and quick orientation. Featuring built-in cybersecurity such as signed firmware and secure boot it ensures the integrity and authenticity of the firmware. Axis Zipstream with H.264/ H.265 significantly reduces bandwidth and storage requirements. Furthermore, AXIS Object Analytics offers highly granular and nuanced object classification.

- > [UHD 4K with 20x optical zoom](#)
- > [Outstanding images with great details](#)
- > [Zipstream with support for H.264/H.265](#)
- > [AXIS Object Analytics](#)
- > [Built-in cybersecurity features](#)



AXIS Q6078-E PTZ Camera

Camera	
Models	AXIS Q6078-E 50 Hz AXIS Q6078-E 60 Hz
Image sensor	1/2.5" progressive scan RGB CMOS
Lens	4.4–88.4 mm, F2.0–3.8 Horizontal field of view: 68.3°–4.2° Vertical field of view: 42.1°–2.34° Autofocus, P-iris control
Day and night	Automatically removable infrared-cut filter
Minimum illumination	Color: 0.2 lux at 30 IRE, F2.0 B/W: 0.002 lux at 30 IRE, F2.0
Shutter speed	1/10000 s to 1 s
Pan/Tilt/Zoom	Pan: 360° endless, 0.05°–450°/s Tilt: 220°, 0.05°–450°/s Zoom: 20x optical, 12x digital, total 240x zoom E-flip, 256 preset positions, tour recording (max 10, max duration 16 minutes each), guard tour (max 100), control queue, on-screen directional indicator, orientation aid PTZ, set new pan 0°, adjustable zoom speed, focus recall

System on chip (SoC)	
Model	ARTPEC-7
Memory	2 GB RAM, 512 MB Flash
Compute capabilities	Machine learning processing unit (MLPU)

Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG
Resolution	3840x2160 4K 2160p to 320x180
Frame rate	Up to 25/30 fps (50/60 Hz) in 4K Up to 50/60 fps (50/60 Hz) in all other resolutions
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265

Image settings	Manual shutter time, compression, color, brightness, sharpness, WDR – dynamic contrast, white balance, exposure control, exposure zones, fine tuning of behavior at low light, rotation: 0°, 180°, text and image overlay, polygon privacy masks, electronic image stabilization (EIS), freeze on PTZ, defog, backlight compensation, scene profiles
-----------------------	--

Network	
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, Axis Edge Vault, Axis device ID, secure keystore (CC EAL4 certified), TPM (FIPS 140-2 certified)
Supported protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS ^a , TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP ^b , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, NTCIP, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)

System integration	
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-Click Cloud Connection ONVIF [®] Profile G, ONVIF [®] Profile S and ONVIF [®] Profile T, specification at onvif.org
Event conditions	Device status: above operating temperature, above or below operating temperature, below operating temperature, fan failure, IP address removed, network lost, new IP address, shock detected, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: manual trigger, virtual input MQTT subscribe

Event actions	PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: live stream open Day/night mode, overlay text, video recording to edge storage, pre- and post-alarm video buffering, send SNMP trap PTZ: PTZ preset, start/stop guard tour File upload via FTP, SFTP, HTTP, HTTPS network share and email MQTT publish Notification via email, HTTP, HTTPS and TCP
----------------------	---

Data streaming	Event data
Built-in installation aids	Pixel counter, leveling guide

Analytics	
AXIS Object Analytics	Object classes: humans, vehicles Trigger conditions: line crossing, object in area Up to 10 scenarios Metadata visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event

Applications	Included AXIS Object Analytics, AXIS Video Motion Detection, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, autotracking 2, active gatekeeper, AXIS OSDI Zones, Orientation Aid PTZ Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
---------------------	---

General	
Casing	IP66-, IP67-, NEMA 4X- and IK10-rated Metal casing (aluminum), polycarbonate (PC) clear dome, sunshield (ASA)

Sustainability	PVC free
-----------------------	----------

Power	Axis High PoE 60 W SFP midspan: 100–240 V AC, max 66.1 W Camera consumption: typical 16 W, max 51 W
--------------	--

Connectors	RJ45 10BASE-T/100BASE-TX PoE, RJ45 Push-pull Connector (IP66/IP67) included
-------------------	---

Storage	Support for SD/SDHC/SDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
----------------	--

Operating conditions	With 30 W: -20 °C to 50 °C (-4 °F to 122 °F) With 60 W: -50 °C to 50 °C (-58 °F to 122 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Arctic Temperature Control: Start-up as low as -40 °C (-40 °F) Humidity 10–100% RH (condensing)
-----------------------------	---

Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
---------------------------	------------------------------------

Approvals	EMC EN 55032 Class A, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35 EN 50121-4, IEC 62236-4
------------------	---

Safety	IEC/EN/UL 60950-1 IEC/EN/UL 60950-22, IEC/EN/UL 62368-1, IS 13252
---------------	--

Environment	IEC/EN 60529 IP66/IP67, NEMA TS 2 (2.2.7-2.2.9), IEC 62262 IK10, ISO 4892-2, EN 50121-4, IEC 62236-4, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-60, IEC 60068-2-78, NEMA 250 Type 4X
--------------------	---

Network	NIST SP500-267 Midspan: EN 60950-1, GS, UL, cUL, CE, FCC, VCCI, CB, KCC, UL-AR
----------------	--

Weight	3.75 kg (8.3 lb)
---------------	------------------

Dimensions	Ø232 x 271 mm (Ø9 1/8 x 10.7 in)
Included accessories	Axis High PoE 60 W SFP midspan 1-port, RJ45 Push-pull Connector (IP66), Sunshield Installation Guide, Windows decoder 1-user license
Optional accessories	Smoked dome cover AXIS T91 Mounting Accessories, AXIS T8415 Wireless Installation Tool, AXIS T90 Illuminators, AXIS T8310 Video Surveillance Control Board, multi-user decoder license pack
Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/vms

Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese

Warranty 5-year warranty, see axis.com/warranty

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*

Environmental responsibility:

axis.com/environmental-responsibility