

TP-LINK DECO X20-DSL 2-PACK Dual-band (2.4 GHz / 5 GHz) Wi-Fi 6 (802.11ax) White 3 Internal

Brand: TP-LINK Product code: DECO X20-DSL(2-PACK)

Product name: DECO X20-DSL 2-PACK

- VDSL Modem Router + Mesh WiFi Save a modem, and gaining a better WiFi experience
- Super VDSL2 Speed Supports Profile 35b tech to deliver downstream up to 350 Mbps
- Superior WiFi 6 speeds up to 1.8 Gbps 1201 Mbps (5 GHz) and 574 Mbps (2.4 GHz) dual-band WiFi with WiFi 6 technology
- Fully Gigabit Ethernet 4x Gigabit WAN/LAN Ethernet ports provide flexible internet access at warp speed
- TP-Link HomeShield Real-time IoT and network protection, robust Parental Controls, and comprehensive reports
- True Seamless Roaming Mesh WiFi Walk through your home and stay connected with the fastest possible speeds

AX1800, 2.4 / 5 GHz, 802.11 a/b/g/n/ac/ax, 1.5 GHz Quad-Core CPU, 4x Gigabit LAN, 1x DSL, 105 \times 167mm





Design		Features	
Housing colour * LED indicators Antenna type * Antennas quantity Number of devices supported Transmit power Reset button	White Power Internal 2 150 CE: ≤20 dBm (2.4GHz), ≤23 dBm (5GHz) ✓ 0 - 40 °C	Features Built-in processor Processor cores Processor frequency Quality of Service (QoS) support Port forwarding Firewall security BeamForming Number of guest networks (5 GHz) Number of guest networks (2.4	4 1.5 GHz ✓ SPI Firewall ✓
Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-40 - 60 °C 10 - 90% 5 - 90%	GHz) Parental control Firmware upgradeable via MU-MIMO technology	1 Network
Wireless LAN features	D 11 1/2 4 011 (5 011)	MIMO	4
	Dual-band (2.4 GHz / 5 GHz) Wi-Fi 6 (802.11ax)	Operating modes	DSL, Router, Access Point
Wi-Fi standards	802.11a,802.11b,802.11g,Wi-Fi 4 (802.11n),Wi-Fi 5 (802.11ac),Wi-Fi 6 (802.11ax)	Protocols DHCP client DHCP server	✓
WI AN data transfer rate (second	1201 Mbit/s 574 Mbit/s	Ports & interfaces	
Networking standards	IEEE 802.11a,IEEE 802.11ac,IEEE 802.11ax,IEEE 802.11b,IEEE 802.11g,IEEE 802.11k,IEEE 802.11n,IEEE 802.11v	Ethernet LAN (RJ-45) ports * Ethernet WAN DC-in jack	3 ✓ ✓
	WPA,WPA2-PSK,WPA3	Power AC adapter input voltage AC adapter frequency AC adapter input current AC adapter output voltage AC adapter output current	100 - 240 V 50/60 Hz 0.6 A 12 V 1.5 A
IGMP snooping Tagged VLAN Dynamic DNS (DDNS)	4 4 4	Weight & dimensions Width Depth	105 mm 105 mm

Wireless LAN features		Weight & dimensions	
Guest access	✓	Height	167 mm
Control apps supported	TP-Link Deco	Packaging content	
DSL features		Number of products included	2 pc(s)
ADSL	✓	AC adapter included	✓
ADSL2	✓		
ADSL2+	✓		
VDSL2	✓		

