## **Product Specification**


Model: ND65PNA


## **Product Feature**



- 1. Revolutionary Performance:
- ♦ Mainboard HV8386
- ♦ DDR4 3GB Memory & 16GB Storage
- ♦ WIFI Module(Optional)
- ♦ PC Module (OPS,Optional)
- 2. Visual Revolution:
- ♦ 4K Resolution
- ♦ 450cd/m² Brightness
- ♦ 4K HDMI OUT

## Dimension







-		-	_	-	-		-	 	
	HINNE	8.8		90		100		1101111	0

Display	
Size	65 inch
Panel type	ADS
Response Time	8ms
Aspect Ratio	16:9
Display Area	1428.48(H)×803.52(V)mm
Pixel Pitch	0.372×0.372mm
Resolution	3840(H)×2160(V)
Refreshing Frequency	60Hz
Display Color	1.07B(10bit)
Operation Hour	16/7
Contrast Ratio	1200:1
Viewing Angle	178°(H/V)
Back Light Unit	DLED
Brightness (min)	400cd/m <sup>2</sup>
Brightness (typ)	450cd/m <sup>2</sup>
Life Time	≥30000 Hours
Android System	
System Version	Android 8.0
CPU	ARM 2*A73+2*A53 1.1GHz Quad Core

GPU	G51 Dual Core			
RAM	3GB			
ROM	16GB			
Audio				
Sound Channel	2.0			
Output Power	2×12W			
Power				
Power Requirements	100-240V ~ 50/60Hz, 3A			
Overall Power(Max.)	300W			
Standby Power	≤0.5W			
I/O port				
HDMI IN	2			
HDMI OUT(optional)	1			
USB 2.0	2			
USB 3.0	1			
DP IN	1			
VGA IN	1			
AUDIO IN	1			
AUDIO OUT	1			
SPDIF	1			
LAN IN	1			
RS232	1			
Button Location & quantity	Back physical keys,7			
Physical Specification				
Dimension L×H×D	1451×828×78.5mm			
Dimension (package) L×W×H	1605×220×965mm			
Thickness of bezel	Bottom 13mm, edge 9mm			
Wall-hanging Screw Spec	M6×12mm			

VESA	400×200mm				
Net Weight	22.95kg				
Gross Weight	33.6kg				
Accessories					
Power Cord	×1				
Power Adapter	×1				
Remote Control	×1				
WiFi Module	×1				
Wall Mount	×1				
Environmental Conditions					
Operation Temperature	0°C - 40°C				
Operation Humidity	10% - 90%RH				
Storage Temperature	-20°C -60°C				
Storage Humidity	10% - 90%RH				

## Statement

Altitude

The product pictures of this specification only indicate that there may be slight difference in product effects (included but not limited to appearance, color and size). Please refer to the product.

Below 5000 meters

Due to the influence of product configuration and manufacturing process, the actual size/weight of the fuselage may differ.

In order to provide accurate specification parameters and product characteristics as much as possible, it is possible to adjust and revise the text description and picture effect of this specification in real time, so as to match the actual product performance, specifications and other information.

No special notice will be given if necessary.