

# AX1800 Wi-Fi 6 ADSL2/VDSL2+ Modem Router with VoIP

DSL-X1852E

- Wi-Fi 6 (802.11ax) technology provides faster speeds, greater capacity and less network congestion
- Wi-Fi speeds up to 1.8 Gbps (600 + 1200Mbps) built for the modern device-dense Smart Home
- Dual-band Wi-Fi makes 4K streaming, gaming and video chatting a breeze
- 4 Gigabit Ethernet LAN ports and 1 Gigabit Ethernet WAN port provides optional wired connectivity
- BSS colouring helps organise data packets, making your network more efficient and improving overall Wi-Fi 6 performance
- Voice over IP technology with advanced communication features



## Wi-Fi 6

Perfect for 4K streaming, VR gaming, video calling and keeping all your smart home devices connected.



## D-Link Wi-Fi

Seamlessly connects your devices to the strongest signal as you move from room to room.



## OFDMA

Perfect for Smart Homes filled with bandwidth-hungry IoT devices battling for bandwidth.



## Smart Steering

Automatically steers your devices to the optimal wireless band, ensuring you're always connected to fast, reliable Wi-Fi.



## Profile-based Parental Controls

Assign devices to profiles to individually block websites, set schedules for access, and turn off Wi-Fi.



## Voice Over IP

Connect ordinary phone sets to the FXS ports to make VoIP phone calls.

## Technical Specifications

DSL-X1852E

### General

Device Interfaces	4 x Gigabit Ethernet LAN ports, 1 x Gigabit Ethernet WAN port, 1 x RJ-11 xDSL port, 2 x FXS VoIP ports, 1 x USB 3.0 port, IEEE 802.11 ax <sup>1</sup> /ac/n/g/b/a wireless LAN
LED	Power, Internet, 2.4GHz Wi-Fi, 5GHz Wi-Fi, USB 3.0, LAN
Antenna Type	Four external antennas
Wi-Fi Data Rate	2.4GHz Up to 600Mbps <sup>2</sup> , 5GHz Up to 1200Mbps <sup>2</sup>
IEEE Standard	IEEE 802.11ax/ac/n/g/b/k/v/a, IEEE 802.3u/ab
Minimum Requirements	Windows 10/8.1/8/7/Vista or Mac OS X 10.6 or higher, Supports Internet Explorer 10/Firefox 28.0/Chrome 28.0/Safari 6.0 and up, Network Interface Card

### Functionality

Security Protocol	WPA2 (Wi-Fi Protected Access), WPA3(Wi-Fi Protected Access), WPS (Wi-Fi Protected Setup)
Firewall	DoS, Stateful Packet Inspection, Anti-spoofing Checking, IP/MAC Address Filtering, 1 x DMZ
QoS	D-Link Intelligent QoS Technology
Speed Test	Ookla SpeedTest

### Software

Device Management	Web UI
-------------------	--------

### Physical

Dimensions	251.64 x 166.47 x 194.18 mm (9.90 x 6.55 x 7.64 in)
Weight	485.6 grams (1.073 pounds)
Power Adapter	12V/2A
Operating Temperature	5 to 40 °C
Storage Temperature	-20 to 70 °C
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Certifications	CE , RCM, Telepermit

### Ordering Information

DSL-X1852E	AX1800 Wi-Fi 6 ADSL2/VDSL2+ Modem Router with VoIP
------------	--

<sup>1</sup>The DSL-X1852E may not support all of the mandatory features, established in Wave 1 of the IEEE 802.11ax specifications

<sup>2</sup> Maximum wireless signal rate derived from IEEE Standard 802.11ax specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead, may lower actual data throughput rate. Environmental factors will adversely affect wireless signal range.

