

TSW114

GIGABIT DIN RAIL SWITCH

// TSW114 is an affordable way to simplify your connectivity with its integrated DIN-rail bracket and plug-n-play nature.

// 5 x Gigabit Ethernet ports provide stable, reliable connectivity for high-bandwidth solutions with multiple Ethernet devices.

// Compact size, front-facing ports, and integrated DIN rail bracket enable easy installation across many industrial environments.

// Rugged anodized aluminum housing and a wide power supply voltage range of 9-30 V make this unmanaged switch perfect for industrial solutions.



EASY MOUNTING

Integrated DIN rail bracket and front-facing ports

GIGABIT ETHERNET

5 x Gigabit Ethernet ports with speeds of up to 1000 Mbps

COMPACT & DURABLE

Rugged anodized aluminum housing that fits in your pocket

PLUG-N-PLAY

No additional configuration needed



KEY FEATURES

HARDWARE

Power supply	2-pin industrial DC power socket, 9 - 30 VDC
Power consumption	Idle: 0.3 W / Max: 2.3 W
Status LEDs	1 x Power LED, 10 x LAN status LEDs
Ethernet	5 x RJ45 ports, 10/100/1000 Mbps
Ingress protection rating	IP30
Operating temperature	-40 °C to 75 °C
Housing	Anodized aluminum housing and panels
Dimensions	113.1 x 27.4 x 80.5 mm
Weight	174 g
Installation	Integrated DIN rail bracket, wall mounting (additional kit needed), flat surface placement

PERFORMANCE SPECIFICATIONS

Bandwidth (Non-blocking)	10 Gbps
Packet buffer	128 KB
MAC address table size	2K entries
Jumbo frame support	9216 bytes

FRONT VIEW

BACK VIEW

