BE9300 Tri-Band Wi-Fi 7 Router Model: MR47BE

Highlights

- Amazing 9.3 Gbps Tri-Band Wi-Fi 7⁺
- 6× Omni Directional Antennas for Wider Coverage
- 4×2.5 Gbps Ports for Higher Performance[§]
- More Capacity over 300 Devices[†]
- 4× Lower Latency[△]
- Enhanced WPA3 Security**
- Easy Setup with the MERCUSYS App







Applications





Ideal for average Internet users seeking fast downloads, seamless streaming audio, uninterrupted streaming video, and lag-free online gaming

Features



Parental Controls Establish appropriate policies to protect children with responsible, safe internet access



Guest Network Provides a separate network for guests to ensure your security and privacy



Quality of Service Prioritizes devices you select to perform better



Access Point Mode Extends a wired network and makes it wireless



IPTV Support Supports IGMP Proxy/Snooping, Bridge, and Tag VLAN to optimize IPTV streaming



IPv6 Support Allows you to visit IPv6 websites and enjoy IPv6 services provided by your ISP



Wi-Fi 7 — Take Your Home Network to the Next Level

Multi-Link Operation





Amazing 9.3 Gbps Tri-Band Wi-Fi

Wi-Fi 7 takes full advantage of the 6 GHz band, with up to 320 MHz channels, 4K-QAM, and MLO(Multi-Link Operation), improving Wi-Fi speeds to 9.3 Gbps. Experience unlimited 8K streaming and lightning-fast downloading.^{†‡}



More Fluid with 4× Lower Latency

Offering 4× less latency than Wi-Fi 6/6E routers, applications like VR/AR, video conferencing, and online gaming consistently perform at optimal efficiency.[△]



Connect over 300 Devices

Concurrently uses MU-MIMO and tri-band to communicate with numerous devices. Wi-Fi 7 delivers unobstructed signals to your laptop, TV, and IoT devices when combined with the potent CPU.⁺

// Wider Wi-Fi Coverage

6× omni directional antennas, proprietary Wi-Fi optimization, and Beamforming technology deliver broader coverage, more capacity, stronger and more reliable connections, and less interference.



MR47BE with Beamforming

I Overall Security Protection

The latest security standard, WPA3, provides improved comprehensive Wi-Fi protection to defend your devices and private information against brute-force attacks.**



Regular Router without Beamforming

// Full 2.5 Gbps Ports

Equipped with 1× 2.5 Gbps WAN port and 3× 2.5 Gbps LAN ports, MR47BE allows you to take full advantage of your broadband speed. Plug your PCs, smart TVs, game consoles, or NAS devices into the ports for blazing-fast wired connections. \S





MERCUSYS[®]

Specifications

Hardware

Ports 1× 2.5 Gbps WAN Port + 3× 2.5 Gbps LAN Ports[§] Button Reset/WPS Button Dimensions 10.1×4.7×1.7 in (258×119×43.3 mm) Antennas 6× Omni Directional Antennas



Power — LAN Ports: Connect to Desktops, Game Consoles, etc.

Wireless

Wireless

5760 Mbps (6 GHz) +2880 Mbps (5 GHz)+574 Mbps (2.4 GHz)[†] Wi-Fi 7 Features 6 GHz, EHT320, 4K-QAM, Multi RU, OFDMA, MU-MIMO, MLO (Multi-Link Operation)[‡]

Advanced Features

IPTV, IPv6, Access Point Mode, DHCP Server, and Smart Connect

EIRP

2.4 GHz \leq 20dBm (EIRP) 5 GHz \leq 23dBm (band1, band2) 5 GHz \leq 30dBm (band3) 6GHz \leq 23 dBm (EIRP)

Reception Sensitivity:

2.4 GHz:

11ax HE20 MCS0: -95dBm, 11ax HE20 MCS11: -65dBm 11ax HE40 MCS0: -93dBm, 11ax HE40 MCS11: -63dBm 5 GHz:

11ax HE20 MCS0:-95dBm, 11ax HE20 MCS11:-64dBm 11ax HE40 MCS0:-93dBm, 11ax HE40 MCS11:-62dBm 11ax HE80 MCS0:-89dBm, 11ax HE80 MCS11:-59dBm 11ax HE160 MCS0:-85dBm, 11ax HE160 MCS11:-56dBm 11be EHT20 MCS13:-58dBm, 11be EHT40 MCS13:-56dBm 11be EHT80 MCS13:-53dBm, 11be EHT160 MCS13:-51dBm

6 GHz:

11ax HE20 MCS0:-95dBm, 11ax HE20 MCS11:-65dBm 11ax HE40 MCS0:-93dBm, 11ax HE40 MCS11:-63dBm 11ax HE80 MCS0:-90dBm, 11ax HE80 MCS11:-60dBm 11ax HE160 MCS0:-87dBm, 11ax HE160 MCS11:-58dBm 11be EHT20 MCS13:-60dBm, 11be EHT40 MCS13:-58dBm 11be EHT80 MCS13:-54dBm, 11be EHT160 MCS13:-52dBm 11be EHT320 MCS0:-84dBm, 11be EHT320 MCS13:-48dBm **Wireless Function**

Enable/Disable Wireless Radio, WMM

Security Features

- Wireless Security: WPA-PSK/WPA2-PSK/ WPA3-SAE**
- Guest Network Access
- Firewall Protection
- VPN Support: OpenVPN/PPTP/L2TP/ WireGuard VPN Server and Clients

Specifications

Software

WAN TypeFDynamic IP/Static IP/PPPoE/L2TP/PPTPIDHCPGServer, DHCP Client ListANAT ForwardingIPort Forwarding, Port Triggering, UPnP, DMZMManagementGAccess ControlGLocal ManagementIRemote ManagementIFirewall SecuritySPI Firewall, IP and MAC Address BindingGuest Network2.4 GHz Guest Network, 5 GHz Guest Network,6 GHz Guest NetworkI

© 2023 MERCUSYS

¹Maximum wireless signal rates are the physical rates derived from IEEE Standard 802.11 specifications. Over 300 device connections is based on laboratory test data, which analyzed the connections of different devices on the 6 GHz, 5 GHz, and 2.4 GHz bands simultaneously. These devices simulated a typical home scenario by running simultaneous applications in the same room that included 4K video, 1080p video, 720p video, file downloading, web browsing, IP cameras, and other IoT devices. Actual wireless data throughput, wireless coverage, and connected devices are not guaranteed and will vary as a result of internet service provider factors, network conditions, client limitations, and environmental factors, and building materials, obstacles, volume and density of traffic, and client location.

[‡]Use of Wi-Fi 7 (802.11be), Wi-Fi 6 (802.11ax), and features including Multi-Link Operation (MLO), 320 MHz Bandwidth, 4K-QAM, Multi-RUs, OFDMA, and MU-MIMO requires clients to also support the corresponding features. The 320 MHz bandwidth is only available on the 6 GHz band. Simultaneously, the 320 MHz bandwidth on the 6 GHz band and 160 MHz bandwidth on the 5 GHz band may be unavailable in some regions/countries due to regulatory restrictions. Double channel width and speed refer to 320 MHz compared to 160 MHz for Wi-Fi 6 routers. This router may not support all the mandatory features as ratified in the IEEE 802.11be specification. Further software upgrades for feature availability may be required.

§2.5 Gbps internet speeds require compatible service plans and equipment.

⁻4× Lower Latency refers to the latency improvement of Wi-Fi 7 routers compared to Wi-Fi 6/6E routers, based on laboratory test data. The test conditions had the same 5 GHz or 6 GHz single-frequency wireless interference and tested the maximum latencies of Wi-Fi 7 clients (with MLO turned on) connecting to the 5 GHz and 6 GHz bands of a MERCUSYS Wi-Fi 7 router (with MLO turned on) simultaneously and to the 5 GHz or 6 GHz bands of a Wi-Fi 6/6E router (without the MLO function).

*EasyMesh-compatible products can network with other devices that use EasyMesh. Failed connections may be due to firmware conflicts of different vendors. The EasyMesh-compatible function is still being developed on some models and will be supported in subsequent software updates.

**Use of WPA3 requires clients to also support the corresponding feature.

Actual network speed may be limited by the rate of the product's Ethernet WAN or LAN port, the rate supported by the network cable, internet service provider factors, and other environmental conditions.

Protocols IPv4, IPv6 Cloud Service Auto Firmware Upgrade, Mercusys ID, DDNS DDNS Mercusys, NO-IP, DynDNS Quality of Service QoS by Device EasyMesh Supported Parental Controls Supported

Others

Package Contents

- BE9300 Tri-Band Wi-Fi 7 Router MR47BE
- Power Adapter
- Quick Installation Guide
- RJ45 Ethernet Cable

Environment

- Operating Temperature: 0°C~40°C (32°F~104°F)
- Operating Humidity: 10%~90% Non-Condensing
- Storage Humidity: 5%~90% Non-Condensing