D-Link

D-Link DSL-226 wireless router Fast Ethernet Single-band (2.4 GHz) White

Brand : D-Link Product code: DSL-226

Product name: DSL-226

Wireless N300 VDSL2/ ADSL2+ Modem Router

D-Link DSL-226 wireless router Fast Ethernet Single-band (2.4 GHz) White:

The DSL-226 Wireless N300 VDSL2/ ADSL2+ Modem Router is everything you need for reliable Internet access throughout your entire home or office. It delivers premium performance for users who demand reliable Wi-Fi speeds for streaming and downloading.

D-Link DSL-226. WAN connection type: RJ-45. Wi-Fi band: Single-band (2.4 GHz), Top Wi-Fi standard: Wi-Fi 4 (802.11n), WLAN data transfer rate (max): 300 Mbit/s. Ethernet LAN interface type: Fast Ethernet, Cabling technology: 10/100Base-T(X), Networking standards: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3i, IEEE 802.3u. Security algorithms: 64-bit WEP, 128-bit WEP, WPA, WPA2, WPS. Product type: Tabletop router, Product colour: White





WAN connection		Security		
Ethernet WAN * DSL WAN *	√	Stateful Packet Inspection (SPI) Network address translation (NAT)	4	
SIM card slot *	X DI 45	Protocols		
WAN connection type	RJ-45	Universal Plug and Play (UPnP)	✓	
Wireless LAN features		Design		
Wi-Fi band * Top Wi-Fi standard * WLAN data transfer rate (max) * Wi-Fi standards	Single-band (2.4 GHz) Wi-Fi 4 (802.11n) 300 Mbit/s 802.11b, 802.11g, Wi-Fi 4 (802.11n)	Product colour On/off switch Product type *	White ✓ Tabletop router	
Network	. 5,	Sustainability		
Ethernet LAN *	1	Sustainability certificates	CE, RoHS	
Ethernet LAN interface type *	Fast Ethernet	Antenna		
Cabling technology	10/100Base-T(X)	Antenna design *	External	
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3i, IEEE 802.3u	Power		
Wireless Distribution System (WDS)	J	Power source type *	DC	
bridge VPN Passthrough	,	Operational conditions		
3	*	Operating temperature (T-T)	0 - 40 °C	
Ports & interfaces		Storage temperature (T-T)	-20 - 70 °C	
Ethernet LAN (RJ-45) ports * USB port *	4	Operating relative humidity (H-H)	5 - 95%	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	•	System requirements		
ports quantity DC-in jack	1	Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows Vista, Windows XP	
Management features			Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12	
Quality of Service (QoS) support	1		Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.7.5	
WPS push button	✓			
Security		Mac operating systems supported		
Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA2, WPS		Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura	

Weig	ht	&	dim	ensions

 Width
 141,2 mm

 Depth
 100,1 mm

 Height
 35 mm

 Weight
 150 g

