

LG 55UH5J-H signage display Digital signage flat panel 139,7 cm (55") IPS Wi-Fi 500 cd/m 2 UHD+ Black 24/7


Brand: LG Product code: 55UH5J-H

Product name: 55UH5J-H

55", IPS, 16 : 9, 1100:1, 3840 x 2160, 500 cd/m², 60Hz, 178 X 178 °, 8ms, 95%, 1234.4 x 720.9 x 39.9 mm, 19000 g, black

LG 55UH5J-H. Product design: Digital signage flat panel. Display diagonal: 139,7 cm (55"), Display technology: IPS, Display resolution: 3840 x 2160 pixels, Display brightness: 500 cd/m², HD type: UHD+. Wi-Fi. Operating hours (hours/days): 24/7. Product colour: Black






Display resolution 3840 x 2160 pixels 500 cd/m²				
Display diagonal 139,7 cm (55°) Number of OSD languages 19 Display technology IPS Number of OSD languages 19 Arabic, Simplified Chin Traditional Chinese, Cz German, Dutch, English (Display brightness 500 cd/m² On Screen Display (OSD) languages Finnish, French, Greek, Nowagian, Portuguese Swedish, Turkish (Spilay brightness 16,9 Operating hours (hours/days) 24/7 Availate (April 100-1) HDCP Vocational (International Protection (IP) code IPSX Ontrast ratio (typical) 1100-1 HDCP Vocational (IP) code IPSX International Protection (IP) code I	play		Performance	
Display technology	backlighting type	Edge-LED	Purpose *	Universal
Display resolution Saku x 2160 pixels Display brightness 500 cd/m² On Screen Display (OSD) languages Finish, French, Greek, Norwegian, Portuguese Swedish, Turkish Portuguese Swedish, Turkish Finish, French, Greek, Norwegian, Portuguese Swedish, Turkish Portuguese Swedish, Tur	play diagonal *	139,7 cm (55")	Number of OSD languages	19
Response time 8 ms Operating hours (hours/days) 24/7 Contrast ratio (typical) 1100:1 HDCP ✓ Contrast ratio (typical) 1000000:1 International Protection (IP) code IPSX Viewing angle, horizontal 178° HDCP version 1.4 Viewing angle, vertical 178° Power Display number of colours 1.07 billion colours Power consumption (typical) * 110 W Colour saturation 95% Power consumption (off) 0.5 W Rated lifetime 50000 h Power consumption (max) 150 W Native refresh rate 60 Hz AC input voltage 100 - 240 V Haze rate 28% AC input frequency 50 - 60 Hz How ports quantity* 4 Weight & dimensions HDMI ports quantity* 4 Weight & dimensions HDMI ports quantity 3 Depth 39,9 mm HDMI output ports quantity 1 Height 720,9 mm DVI port * √ Weight (with stand) 1234,4 mm USB ports quantity* <td>Display resolution * 3840 x 2160 pixels Display brightness * 500 cd/m² HD type * UHD+</td> <td>3840 x 2160 pixels 500 cd/m² UHD+</td> <td>On Screen Display (OSD) languages</td> <td>Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Japanese, Norwegian, Portuguese, Russian, Swedish, Turkish</td>	Display resolution * 3840 x 2160 pixels Display brightness * 500 cd/m² HD type * UHD+	3840 x 2160 pixels 500 cd/m ² UHD+	On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Japanese, Norwegian, Portuguese, Russian, Swedish, Turkish
Contrast ratio (typical) 1100:1 HDCP ✓ Contrast ratio (dynamic) 1000000:1 International Protection (IP) code IP5X Viewing angle, horizontal 178° HDCP version 1.4 Viewing angle, vertical 178° Power Display number of colours 1.07 billion colours Power consumption (typical) * 110 W Colour saturation 95% Power consumption (off) 0,5 W Rated lifetime 50000 h Power consumption (max) 150 W Native refresh rate 60 Hz AC input voltage 100 · 240 V Hazer rate 28% AC input frequency 50 · 60 Hz Ports & interfaces Heat dissipation 376 BTU/h HDMI ports quantity * 4 Weight & dimensions HDMI ports quantity * 4 Weight & dimensions HDMI input ports quantity 1 1 Height (with \$1234,4 mm DVI port * ✓ Weight 19 kg DisplayPorts quantity 1 1 Width (with stand) 1234,4 mm USB ports quantity 1 1 Height (Operating hours (hours/days)	24/7
Contrast ratio (dynamic) 1000000:1 International Protection (IP) code IP5X Viewing angle, horizontal 178° HDCP version 1.4 Viewing angle, horizontal 178° Power Display number of colours 1.07 billion colours Power consumption (typical)* 110 W Colour saturation 95% Power consumption (off) 0,5 W Rated lifetime 50000 h Power consumption (max) 150 W Native refresh rate 60 Hz AC input voltage 100 - 240 V Haze rate 28% AC input frequency 50 - 60 Hz HDMI ports quantity* 4 Weight & dimensions HDMI ports quantity* 4 Weight & dimensions HDMI input ports quantity 3 Depth 39,9 mm HDMI output ports quantity 1 Height 720,9 mm DVI port* ✓ Weight 19 kg DisplayPorts quantity* 1 Width (with stand) 1234,4 mm USB ports ✓ Depth (with stand) 290 mm USB ports quantity			HDCP	✓
Viewing angle, Norizontal 178° HDCP version 1.4 Viewing angle, vertical 178° Power Display number of colours 1.07 billion colours Power consumption (typical) * 110 W Colour saturation 95% Power consumption (off) 0.5 W Rated lifetime 500000 h Power consumption (max) 150 W Native refresh rate 60 Hz AC input voltage 100 - 240 V Haze rate 28% AC input frequency 50 - 60 Hz Ports & interfaces HDMI ports quantity * 4 Weight & dimensions HDMI ports quantity * 4 Weight & dimensions HDMI input ports quantity 3 Depth 39.9 mm HDMI input ports quantity 1 Height 720.9 mm DVI port * √ Weight 19 kg DisplayPorts quantity * 1 Width (with stand) 1234,4 mm USB ports quantity * 1 Width (with stand) 1234,4 mm USB ports quantity * 1 Weight (with stand) 19.6 kg			International Protection (IP) code	IP5X
Viewing angle, vertical 178° Power Display number of colours 1.07 billion colours Colour saturation 95% Power consumption (typical) * 110 W Rated lifetime 50000 h Power consumption (max) 150 W Native refresh rate 60 Hz AC input voltage 100 - 240 V Haze rate 28% AC input frequency 50 - 60 Hz Heat dissipation 376 BTU/h HDMI ports quantity * 4 Weight & dimensions HDMI version 2.2 Width 1234,4 mm HDMI input ports quantity 1 Depth 39.9 mm HDMI untput ports quantity 1 Weight 19 kg DisplayPorts quantity 1 Weight 19 kg DisplayPorts quantity 1 Weight 19 kg DisplayPorts quantity 1 Weight (with stand) 1234,4 mm USB port 4 Veight 19 kg DisplayPorts quantity 1 Weight (with stand) 290 mm USB ports quantity 1 Weight (with stand) 770,7 mm USB version 2.0/3.2 Gen 1 (3.1 Gen 1) Weight (with stand) 19,6 kg Ethernet LAN * Ethernet LAN (RJ-45) ports 1 Package width 1360 mm Audio (L/R) in 1 Package depth 175 mm Audio (L/R) out 1 Package weight 24,2 kg RS-232 cinterface Version Remote control included Version Remote control included Version Remote control included Version Remote control type ST-653T Design	· •		HDCP version	1.4
Display number of colours 1.07 billion colours Power consumption (typical) 110 W	3 - 3 -,		Power	
HDMI ports quantity * 4 Weight & dimensions HDMI version 2.2 Width 1234,4 mm HDMI input ports quantity 3 Depth 39,9 mm HDMI output ports quantity 1 Height 720,9 mm DVI port * Weight 19 kg DisplayPorts quantity * 1 Width (with stand) 1234,4 mm USB port * Depth (with stand) 290 mm USB ports quantity 1 Height (with stand) 770,7 mm USB version 2.0/3.2 Gen 1 (3.1 Gen 1) Weight (with stand) 19,6 kg Ethernet LAN * Ethernet LAN (RJ-45) ports 1 Wi-Fi * Audio (L/R) in 1 Package width 1360 mm Audio (L/R) out 1 Package height 835 mm Audio (L/R) out 1 Package weight 24,2 kg RS-232	1.07 billion colours colour saturation 25% ated lifetime 50000 h lative refresh rate 60 Hz	Power consumption (off) Power consumption (max) AC input voltage	0,5 W 150 W 100 - 240 V	
HDMI version 2.2 Width 1234,4 mm HDMI input ports quantity 3 Depth 39,9 mm HDMI output ports quantity 1 Height 720,9 mm DVI port *	ts & interfaces		Heat dissipation	376 BTU/h
HDMI input ports quantity HDMI output ports quantity 1 Height 720,9 mm 720,9 mm 7	MI ports quantity *	4	Weight & dimensions	
HDMI input ports quantity HDMI output ports quantity 1 Height 720,9 mm Povice of the stand of	MI version	2.2	Width	1234 4 mm
Ethernet LAN (RJ-45) ports 1 Wi-Fi * Audio (L/R) in 1 Audio (L/R) out 1 RS-232 interface RS-232C Audio Built-in speaker(s) * Design Packaging data Package width 1360 mm 175 mm Package depth 175 mm Package height 835 mm Package weight 24,2 kg Packaging content Remote control included Remote control type ST-653T Operational conditions	HDMI output ports quantity DVI port * DisplayPorts quantity * USB port * USB ports quantity 1 USB version 1 2.0/3.2 Gen 1 (3.1 Gen 1)	1 1 1 2.0/3.2 Gen 1 (3.1 Gen 1)	Height Weight Width (with stand) Depth (with stand) Height (with stand)	39,9 mm 720,9 mm 19 kg 1234,4 mm 290 mm 770,7 mm
Wi-Fi *			Packaging data	
RS-232C ✓ Packaging content Audio Remote control included ✓ Remote control type ST-653T Design Operational conditions	Fi * lio (L/R) in lio (L/R) out	v 1 1	Package depth Package height	175 mm 835 mm
Audio Remote control included Built-in speaker(s) * ✓ Remote control type ST-653T Operational conditions Operational conditions			Packaging content	
Built-in speaker(s) * Remote control type ST-653T Design Operational conditions			5 5	1
Design Operational conditions		√		
Openshing temps and the CTT 0 A0 90	·		Operational conditions	
Product design * Digital signage flat panel Operating temperature (1-1) 0 - 40 °C		Digital signage flat panel	Operating temperature (T-T)	0 - 40 °C

Design		Operational conditions	
Placement supported *	Indoor	Operating relative humidity (H-H)	10 - 80%
Orientation	Horizontal/Vertical	Certificates	
Product colour * Black VESA mounting * Panel mounting interface 300 x 300 mm Mounting type Wall	Black ✓	Certification	CB / NRTL, FCC Class "A" / CE / KC, ErP
		Technical details	
		Internal memory	16 MB
		Other features	
		Power consumption (PowerSave)	77 W







0195174033791



195174033791



8806091655035

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.