

Lindy 36470 HDMI cable 0,5 m HDMI Type A (Standard) Black

Brand: Lindy Product code: 36470

Product name: 0.5m High Speed HDMI Cable, Black Line

- Entry level High Speed HDMI 2.0 cable for home and small office applications
- Supports UHD resolutions up to 4096x2160@60Hz 4:4:4 8bit
- Robust PVC housing, nickel connectors, 24K gold plated contacts
- Triple shielded cable, corrosion resistant copper coated steel 30AWG conductors
- HDMI 2.0 compliant: 3D, 4K, 18Gbps, HEC, ARC, CEC, Dolby True HD, DTS-HD Master Audio; HDMI ATC certified; 10 year warranty

0.5m High Speed HDMI Cable, Black Line

Lindy 36470. Cable length: 0,5 m, Connector 1: HDMI Type A (Standard), Connector 1 gender: Male, Connector 2: HDMI Type A (Standard), Connector 2 gender: Male, Connector contacts plating: Gold, HDMI version: 2.0, Maximum resolution: 4096 x 2160 pixels, Data transfer rate: 18 Gbit/s, Product colour: Black





Features		Features	
Cable length * Connector 1 * Connector 2 * Connector 1 gender * Connector 2 gender * Connector 1 form factor Connector 2 form factor	0,5 m HDMI Type A (Standard) HDMI Type A (Standard) Male Male Straight Straight	Cable type Cable jacket material Shield material Bending radius (min) Colour depth Colour sampling	Round cable Polyvinyl chloride (PVC) Aluminium 6 cm 8 bit 4:4:4 300kHz-825MHz 5dB, 825MHz-2.475GHz 5dB.
Product colour * HDMI version Supported graphics resolutions HDMI Ethernet channel Data transfer rate Maximum resolution Maximum refresh rate AWG wire size	version 2.0 rted graphics resolutions 4096 x 2160 Ethernet channel ✓ ransfer rate 18 Gbit/s num resolution 4096 x 2160 pixels num refresh rate 60 Hz vire size 30 ct material Phosphor bronze ctor contacts plating * Gold ctor housing material Polyvinyl chloride (PVC) ctor material Nickel	Nominal attenuation Certification Quantity per pack * Operational conditions Operating temperature (T-T) Storage temperature (T-T)	2.475GHz-4.125GHz 12dB, 4.125GHz-5.1GHz 20dB RoHS, REACH, UL 1 pc(s) -10 - 80 °C -10 - 80 °C
Contact material Connector contacts plating * Connector housing material Connector material Cable material		Weight & dimensions Cable diameter Connector 1 dimensions (WxDxH) Connector 2 dimensions (WxDxH) Package type	6 mm 19,2 x 34,1 x 10,6 mm 19,2 x 34,1 x 10,6 mm Polybag
		Logistics data Harmonized System (HS) code	84733080



4002888364706

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.