



## Lindy 36964 HDMI cable 3 m HDMI Type A (Standard) Black, Grey

**Brand :** Lindy

**Product code:** 36964

**Product name :** 3m High Speed HDMI Cable, Anthra Line

- Professional choice High Speed HDMI 2.0 cable for commercial and high performance AV and IT installations
- Supports UHD resolutions up to 4096x2160@60Hz and HDTV resolutions up to 1080p
- Robust PVC housing, 24K gold plated connectors and contacts
- Triple shielded cable, corrosion resistant tinned copper 30AWG conductors
- HDMI 2.0 compliant: 3D, 4K, 18Gbps, HEC, ARC, CEC, Dolby® True HD, DTS-HD Master Audio; HDMI ATC certified; 10 year warranty

3m HDMI High Speed HDMI Cable, Anthra Line

Lindy 36964. Cable length: 3 m, Connector 1: HDMI Type A (Standard), Connector 1 gender: Male, Connector 2: HDMI Type A (Standard), Connector 2 gender: Male, Connector contacts plating: Gold, Maximum resolution: 4096 x 2160 pixels, Data transfer rate: 18 Gbit/s, Product colour: Black, Grey



### Features

Cable length *	3 m
Connector 1 *	HDMI Type A (Standard)
Connector 2 *	HDMI Type A (Standard)
Connector 1 gender *	Male
Connector 2 gender *	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Product colour *	Black, Grey
Supported graphics resolutions	4096 x 2160
Supported video modes	2160p
HDMI Ethernet channel	✓
Data transfer rate	18 Gbit/s
Maximum resolution	4096 x 2160 pixels
AWG wire size	30
Contact material	Phosphor copper
Connector contacts plating *	Gold
Connector housing material	Polyvinyl chloride (PVC)
Connector material	Gold
Cable material	Copper
Cable type	Round cable
Cable jacket material	Polyvinyl chloride (PVC)

### Features

Shield material	Copper
Bending radius (min)	4,8 cm
Colour depth	8 bit
Plug and Play	✓
Colour sampling	4:4:4
	300kHz-825MHz <5dB 825MHz-2.475GHz <5dB 2.475GHz-4.125GHz <12dB 4.125GHz-5.1GHz <20dB
Nominal attenuation	
Certification	RoHS, REACH, UL, ATC
Quantity per pack *	1 pc(s)

### Operational conditions

Operating temperature (T-T)	-10 - 80 °C
Storage temperature (T-T)	-10 - 80 °C

### Weight & dimensions

Cable diameter	6 mm
Connector 1 dimensions (WxDxH)	20 x 34,2 x 10,9 mm
Connector 2 dimensions (WxDxH)	20 x 34,2 x 10,9 mm
Package type	Polybag

### Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------



4002888369640

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-AUG-2023. Prints or copies of Information are only valid on the printed Publication date