



TP-Link EAP113-Outdoor 300 Mbit/s White Power over Ethernet (PoE)



Brand : TP-Link

Product code: EAP113-OUTDOOR

Product name : EAP113-Outdoor

- Ideal for Outdoor Environment: IP65 weatherproof enclosure for outdoor Wi-Fi applications
 - Fast Wi-Fi: Up to 300Mbps Wi-Fi with 2x2 MIMO.†
 - Long-Range Coverage: Dedicated high-power amplifier and professional antennas
 - Integrated into Omada SDN: Centralized Cloud Management and Intelligent Monitoring
 - Centralized Management: Cloud access and Omada app for ultra convenience and easy management
 - PoE Support: Support both standard 802.3af and 48V Passive PoE for flexible installations
 - Secure Guest Network: Along with multiple authentication options (SMS/Voucher, etc.) and abundant wireless security technologies
- 300Mbps Wireless N Outdoor Access Point

Features		Design	
2.4 GHz *	✓	Placement *	Pole, Wall
5 GHz *	✗	Product colour *	White
6 GHz *	✗	International Protection (IP) code	IP65
Maximum data transfer rate *	300 Mbit/s	Reset button	✓
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Certification	CE, FCC, RoHS
Wi-Fi Multimedia (WMM)/(WME)	✓	Antenna	
Virtual LAN features	VLAN mapping	Antenna type *	External
Rate limiting	✓	Antenna direction type	Omni-directional
Wireless isolation	✓	Antenna features	Detachable antenna
Quality of Service (QoS) support	✓	Antennas quantity	2
Transmitting power (CE)	20 dBm	Antenna gain level (max)	3 dBi
Transmitting power (FCC)	22 dBm	Weight & dimensions	
Security		Width	214,9 mm
Security algorithms *	64-bit WEP, 128-bit WEP, 152-bit WEP, HTTPS, SNMP, SNMPv2, SSH, WPA, WPA-PSK, WPA2-Enterprise, WPA2-PSK	Depth	46 mm
MAC address filtering	✓	Height	37,7 mm
Service Set Identifier (SSID) features	Multiple SSIDs	Packaging content	
Number of SSID supported	8	Number of products included	1 pc(s)
Access Control List (ACL)	✓	Mounting kit	✓
Management features		Antenna included	✓
Syslog	✓	Operational conditions	
Ports & interfaces		Operating relative humidity (H-H)	10 - 90%
Ethernet LAN (RJ-45) ports *	1	Operating temperature (T-T)	-30 - 65 °C
Power		Storage temperature (T-T)	-40 - 70 °C
Power over Ethernet (PoE) *	✓	Storage relative humidity (H-H)	5 - 90%
Power over Ethernet (PoE) type supported	Passive PoE	Sustainability	
DC voltage range	48 V	Sustainability compliance	✓
		Sustainability certificates	CE, Federal Communications Commission (FCC), RoHS

Power

Power consumption (typical) 4,11 W

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 09-NOV-2023. Prints or copies of Information are only valid on the printed Publication date