



TP-Link ER706W wireless router Gigabit Ethernet Dual-band (2.4 GHz / 5 GHz) Black

Brand : TP-Link

Product code: ER706W

Product name : ER706W

- AX3000 Dual-Band WiFi: Supports 2402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz*
 - 6 Gigabit Ethernet Ports: 1 gigabit SFP and 5 gigabit RJ45 ports provide high-speed wired connectivity
 - Omada Mesh Technology: Seamlessly connects to EAPs that support mesh technology, ideal for large-scale scenarios.**
 - Centralized Management: Cloud access and Omada app for ultra convenience and easy management
 - Boosted Coverage: Triple external antennas extend and concentrate the Wi-Fi signals
 - High-Security VPN: Supports multiple VPN protocols including IPSec / SSL / Wireguard / PPTP / L2TP VPN, helping users to establish remote connections more flexibly.△
 - Abundant Security Features: Advanced firewall policies, DoS defense, IP/MAC/URL filtering, and more security functions protect your network and data
- Omada AX3000 Gigabit VPN Router



WAN connection		Protocols	
Ethernet WAN *	✓	DHCP server	✓
DSL WAN *	✓	Routing protocols	OSPF, RIP
SIM card slot *	✗	Design	
3G/4G USB modem compatibility *	✓	Product colour	Black
Wireless LAN features		Product type *	Desktop/pole router
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Antenna	
WLAN data transfer rate (max) *	2402 Mbit/s	Antenna design *	External
Network		Antenna gain level (max)	4,5 dBi
Ethernet LAN *	✓	Features	
Ethernet LAN interface type *	Gigabit Ethernet	Internal memory	512 MB
Dynamic DNS (DDNS)	✓	Internal memory type	DDR4
VPN tunnels quantity	50	Flash memory	128 MB
Ports & interfaces		Certification	CE, FCC, RoHS
Ethernet LAN (RJ-45) ports *	4	Power	
USB port *	✓	Power source type *	DC
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Output voltage	12 V
Management features		Output current	2 A
Reset button	✓	Power consumption (typical)	11,8 W
MU-MIMO technology	✓	Operational conditions	
MIMO	✓	Operating temperature (T-T)	0 - 40 °C
Security		Storage temperature (T-T)	-40 - 70 °C
Security algorithms	WPA, WPA2, WPA3-Enterprise	Operating relative humidity (H-H)	10 - 90%
Access Control List (ACL)	✓	Storage relative humidity (H-H)	5 - 90%
Network address translation (NAT)	✓	Weight & dimensions	
		Width	226 mm
		Depth	131 mm
		Height	35 mm



4895252500691



4895252500707

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.