



TP-Link TL-SG1210PP network switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Brand : TP-Link

Product code: TL-SG1210PP

Product name : TL-SG1210PP



- 9 × 10/100/1000Mbps RJ45 Ports, 1 × 1000Mbps Combo SFP/RJ45 Port
 - With 2 × PoE++ ports and 6 × PoE+ ports, transfers data and power on one single cable
 - Works with IEEE 802.3af/at/bt compliant PDs
 - 802.1p/DSCP QoS enable smooth latency-sensitive traffic
 - Supports PoE Power up to 30 W for each PoE+ port and 60 W for PoE++ port
 - Supports PoE Power up to 123 W for all PoE ports*
 - Plug and Play, no configuration and installation required
 - Up to 250m data and power transmitting range under Extend Mode**
 - PoE Auto Recovery guarantees stable operation of PoE devices by automatically rebooting the dropped or unresponsive PD devices
 - Isolation Mode allows one-click client traffic separation for higher security and performance
 - Priority Mode guarantees the quality of sensitive applications like video monitoring in critical business areas by prioritizing the data of ports 1-2
- 10-Port Gigabit Desktop Switch with 6-Port PoE+ and 2-Port PoE++



Management features		Design	
Switch type *	Unmanaged	Certification	FCC, CE, RoHS
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	9	Fanless	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power	
Combo SFP ports quantity	1	Power source *	PoE
Network		Input current	2.43 A
Networking standards *	IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Input voltage	53.5 V
10G support *	✗	Power over Ethernet (PoE)	
Copper ethernet cabling technology	10BASE-T, 100BASE-TX	Power over Ethernet (PoE) *	✓
Cable types supported	Cat3, Cat4, Cat5, Cat5e	Power over Ethernet plus (PoE+) ports quantity	8
Flow control support	✓	Power over Ethernet (PoE) power per port	30 W
Auto MDI/MDI-X	✓	Total Power over Ethernet (PoE) budget	123 W
Auto-negotiation	✓	Operational conditions	
MAC address auto-learning supported	✓	Operating temperature (T-T)	0 - 40 °C
MAC address auto-aging supported	✓	Storage temperature (T-T)	-40 - 70 °C
Data transmission		Operating relative humidity (H-H)	10 - 90%
Switching capacity *	20 Gbit/s	Storage relative humidity (H-H)	5 - 90%
MAC address table *	4000 entries	Heat dissipation	482,17 BTU/h
Store-and-forward	✓	Weight & dimensions	
Design		Width	209 mm
Rack mounting *	✗	Depth	126 mm
Product colour	Black	Height	26 mm
LED indicators	✓	Logistics data	
		Harmonized System (HS) code	85176990



4895252500356

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-NOV-2023. Prints or copies of Information are only valid on the printed Publication date