

TP-Link VIGI C230I MINI(2.8MM) security camera Dome IP security camera Indoor & outdoor 2304 x 1296 pixels Ceiling

Brand : TP-Link Product family: VIGI Product code: VIGI C230I MINI(2.8MM)

Product name: VIGI C230I

MINI(2.8MM)

3MP IR Mini Dome Network Camera

TP-Link VIGI C230I MINI(2.8MM). Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling, Product colour: White, Form factor: Dome. Lens viewing angle, horizontal: 106.9°, Lens viewing angle, vertical: 56.9°, Lens viewing angle, diagonal: 127.9°. Sensor type: CMOS, Optical sensor size: 25,4 / 2,8 mm (1 / 2.8"). Fixed focal length: 2,8 mm





Performance		Video	
Type * Placement supported * Connectivity technology *	IP security camera Indoor & outdoor Wired	Highlight Compensation (HLC) Digital Wide Dynamic Range (DWDR)	√
Day/night mode	✓	Audio	
Certification	CE/VCCI/BSMI/KC/ONVIF	Built-in speaker(s)	✓
Design		Built-in microphone	✓
Form factor *	Dome	Network	
Mounting type * Product colour * Housing material IK code	Ceiling White Plastic IK08	Ethernet LAN * Ethernet interface type Supported network protocols	✓ Fast Ethernet TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP,
Camera		140 El 4	SSL/TLS
Lens viewing angle, horizontal	106.9°	Wi-Fi * Bluetooth *	×
Lens viewing angle, vertical Lens viewing angle, diagonal	56.9° 127.9°	Storage	
Image sensor		Built-in HDD *	×
Optical sensor size Sensor type *	25,4 / 2,8 mm (1 / 2.8") CMOS	Card reader integrated Compatible memory cards Maximum memory card size	✓ MicroSD (TransFlash) 256 GB
Lens system		Ports & interfaces	
Fixed focal length	2,8 mm	Ethernet LAN (RJ-45) ports	1
Night vision		Security	
Night vision * Night vision distance LED type	√ 30 m IR	Password protection IP address filtering HTTPS encryption	1 1
Video		Management features	
Maximum resolution *	gapixels * 3 MP	Reset button	1
Total megapixels * Video compression formats		Power	
		Power source type * Power consumption (max)	DC, PoE 7,5 W

Video		Power	
Supported graphics resolutions	320 x 240, 352 x 288, 640 x 480 (VGA), 704 x 576, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296	DC output voltage	12
		Operational conditions	
		Operating temperature (T-T)	-30 - 60 °C
Noise reduction		Weight & dimensions	
Noise reduction technology		Width	114 mm
Image quality adjustment		Depth	58 mm
Back Light Compensation (BLC)	✓	Height	114 mm
		Packaging content	
		Number of cameras *	1

