

ViewSonic® LCD DISPLAY VA3209U-2K


Key Features

- SuperClear® IPS panel
- 2K QHD 2560 X 1440 resolution
- HDMI, Display Port, and USB-C inputs for simple connectivity and 65W power delivery
- Variable Refresh Rate eliminates screen tearing and reduce stuttering
- HDR10 Delivers Stellar Contrast and Color Accuracy



Product Description

The ViewSonic VG3209U-2K is a 32" QHD monitor featuring HDMI, Display Port and USB-C inputs for business and home use. Simplify your work with just one cable that provides audiovisual and 65W power transfer. The FreeSync™, eye-care technology, and various ViewMode presets cater for optimal screen performance and comfortable viewing without tearing or stuttering. Expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at low energy consumption.



Visit Us www.viewsonic.com

DISPLAY

Display Size (in.):	32
Viewable Area (in.):	31.5
Panel Type:	IPS Technology
Resolution:	2560 x 1440
Resolution Type:	QHD (Quad HD)
Static Contrast Ratio:	1,200:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Brightness:	250 cd/m ² (typ)
Colors:	1.07B
Color Space Support:	10 bit (8 bit + FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	4ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	75
Variable Refresh Rate Technology:	Yes
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)
Pixel Size:	0.273 mm (H) x 0.273 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	2560x1440
Mac® Resolution (max):	2560x1440
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	2560x1440

CONNECTOR

USB 3.2 Type C DisplayPort Alt mode only :	1 (65W power charger)
3.5mm Audio Out:	1
HDMI 1.4:	1
DisplayPort:	1
Power in:	DC Socket (Center Positive)

AUDIO

Internal Speakers:	2.5Watts x2
--------------------	-------------

POWER

Eco Mode (Conserve):	24W
Eco Mode (optimized):	30W
Consumption (typical):	37W
Consumption (max):	41W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	External Power Adaptor

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
-----------------------	---

CONTROLS

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	15 ~ 120KHz
Frequency Vertical:	24 ~ 75Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.4), Micro-Packet - Type C
---------------	---

ERGONOMICS

Tilt (Forward/Back):	-5° / 20°
----------------------	-----------

WEIGHT (IMPERIAL)

Net (lbs):	15
Net Without Stand (lbs):	12.3
Gross (lbs):	20.3

WEIGHT (METRIC)

Net (kg):	6.8
Net Without Stand (kg):	5.6
Gross (kg):	9.2

DIMENSIONS (IMPERIAL) (WXHxD)

Packaging (in.):	30.3 x 20.1 x 4.9
Physical (in.):	28.1 x 20.5 x 9.1
Physical Without Stand (in.):	28.1 x 16.8 x 2.3

DIMENSIONS (METRIC) (WXHxD)

Packaging (mm):	770 x 510 x 125
Physical (mm):	714 x 520 x 231
Physical Without Stand (mm):	714 x 428 x 59

GENERAL

Regulations:	RoHS, WEEE, KC, K-MEPS, BIS
--------------	-----------------------------

PACKAGE CONTENTS:	VA3209U-2K x1, 3-pin Mickey Mouse Plug (IEC C5) x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Cable (Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
-------------------	--

Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
-------------------	--

Warranty:	*Warranty offered may differ from market to market
-----------	--