

# ViewSonic® LED DISPLAY VG2748

## Key Features

- vDisplay Manager (gratis download)
- Smalle bezel
- HDMI-, DisplayPort- en VGA-ingenen
- SuperClear® IPS-technologie
- Veelzijdige voet



## Product Description



1. VESA Compatible(Wall mount 100mm x 100mm)
2. Menu Control Panel
3. USB down stream x 2
4. AC In
5. DisplayPort
6. HDMI
7. VGA
8. USB up stream
9. USB down stream x 2

Visit Us  [www.viewsonic.com](http://www.viewsonic.com)

**DISPLAY**

Monitor Size:	27"W (27" Viewable) LCD monitor
Panel Technology:	SuperClear® IPS TFT LCD
Resolution:	FHD 1920 x 1080
Display Area:	597.9(H) x 336.3(V) mm
Aspect Ratio:	16:9
Brightness:	300 cd/m <sup>2</sup> (Typ.)
Contrast Ratio:	1000:1 (Typ.)
Dynamic Contrast Ratio:	50,000,000:1
Viewing Angles:	178 degrees (Typ.) / 178 degrees (Typ.)
Response Time:	GTG: 5ms (Typ.)
Pixel Size:	0.311 (H) x 0.311 (W) mm

**INPUT SIGNAL**

Frequency:	Analog: Fh = 24 ~ 82KHz ; Fv = 50 ~ 75Hz Digital: Fh = 24 ~ 82KHz ; Fv = 24 ~ 75Hz
Sync:	Separate Sync / Composite Sync / Sync on Green / TMD5 / PCI-E

**COMPATIBILITY**

PC:	Windows 7, Windows 8, Windows 8.1, Windows 10 certified
Mac®:	Power Mac tested

**CONNECTOR**

Input:	VGA x 1, HDMI x 1 (v1.4 compatible), DisplayPort 1.2 x 1
--------	--

**AUDIO**

Speaker:	2W x 2
----------	--------

**USB**

Upstream:	USB 3.0 Type B x 1
Downstream:	USB 3.0 Type A x 4

**POWER**

Power:	3-pin plug (CEE22) x 1
Voltage:	AC 100-240V (Universal); 50/60Hz
Consumption:	29.15W
Optimize:	23.06W
Conserve:	18.50W

**ERGONOMICS**

Tilt:	40 ~ -5 degrees
Swivel:	+/-60 degrees
Pivot:	+/-90 degrees

**SPECIAL FEATURES**

Eye Care:	Blue light filter, Flicker Free
-----------	------------------------------------

**WALL MOUNT**

VESA®:	100mm x 100mm
--------	---------------

**OPERATING CONDITIONS**

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

**DIMENSIONS (W X H X D) (MM)**

Physical with stand (mm):	620.7mm (W) x 537.2mm (H) x 202.2 mm (D)
Physical without stand (mm):	620.7 mm (W) x 366.1mm (H) x 51.1 mm (D)
Packaging (mm):	692 mm (W) x 430 mm (H) x 218 mm (D)

**WEIGHT**

Net with stand:	7.3kg
Net without stand:	4.9kg
Gross:	10.1 kg

**REGULATIONS**

cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 8.0, EAC, UkrSEPRO, GS, RCM, GEMS

**PACKAGE CONTENTS**

LCD Display  
Power Cable (1.8m)  
DP to DP Cable (1.8m)  
USB3.0 Upstream Cable (1.8m)  
Quick Start Guide