

Viewsonic VP Series VP3481 LED display 86,4 cm (34") 3440 x 1440 pixels Wide Quad HD+ Black

Brand : Viewsonic

Product family: VP Series

Product code: VP3481

Product name : VP3481

VP3481, 34", 3440x1440, 21:9, 5 ms, VA, HDMI, DP, USB C. RMS 2x 5 W, AC 100-240 V, 809x610x299 mm

Viewsonic VP Series VP3481. Display diagonal: 86,4 cm (34"), Display resolution: 3440 x 1440 pixels, HD type: Wide Quad HD+, Display technology: LED, Response time: 5 ms, Native aspect ratio: 21:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black



Display		Ports & interfaces	
Display diagonal *	86,4 cm (34")	HDMI *	✓
Display resolution *	3440 x 1440 pixels	HDMI ports quantity	2
HD type *	Wide Quad HD+	HDMI version	2.0
Native aspect ratio *	21:9	DisplayPorts quantity	1
Display technology *	LED	DisplayPort version	1.4
Panel type *	VA	Audio input	✗
Touchscreen *	✗	Headphone out *	✓
Display brightness (typical)	400 cd/m ²	Headphone outputs	1
Response time	5 ms	Headphone connectivity	3.5 mm
Anti-glare screen	✓	HDCP	✓
Screen shape *	Curved	AC (power) in	✓
Screen curvature rating	1800R	Ergonomics	
Supported graphics resolutions	640 x 350, 640 x 400, 640 x 480 (VGA), 720 x 400, 720 x 480, 720 x 576, 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 768 (WXGA), 1280 x 800 (WXGA), 1360 x 768 (WXGA), 1366 x 768, 1400 x 1050 (SXGA+), 1400 x 900, 1600 x 1200 (UXGA), 1600 x 900, 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1600, 2048 x 1152, 2560 x 1080, 2560 x 1440, 3440 x 1440	VESA mounting *	✓
Contrast ratio (typical) *	3000:1	Panel mounting interface	100 x 100 mm
Contrast ratio (dynamic)	20000000:1	Cable lock slot *	✓
Maximum refresh rate *	100 Hz	Cable lock slot type	Kensington
Viewing angle, horizontal	178°	Height adjustment *	✓
Viewing angle, vertical	178°	Height adjustment	13 cm
Display number of colours *	16.78 million colours	Swivelling	✓
Pixel pitch	0,232 x 0,232 mm	Swivel angle range	0 - 120°
Horizontal scan range	15 - 135 kHz	Tilt angle range	-6 - 21°
Vertical scan range	24 - 75 Hz	On Screen Display (OSD)	✓
Viewable size, horizontal	79,7 cm	Number of OSD languages	14
Viewable size, vertical	33,4 cm	Plug and Play	✓
Display diagonal (metric)	86,36 cm	Tilt adjustment	✓
Colour depth	8 bit	Power	
sRGB coverage (typical)	113%	Energy efficiency class (SDR) *	G
		Energy efficiency class (HDR) *	G
		Energy consumption (SDR) per 1000 hours *	34 kWh
		Energy consumption (HDR) per 1000 hours *	50 kWh
		Power consumption (typical) *	74,5 W
		Power consumption (standby) *	0,5 W
		Power consumption (off)	0,3 W

Display		Power	
NTSC coverage (typical)	80%	Power consumption (PowerSave)	53,5 W
Adobe RGB coverage	84%	AC input voltage	100 - 240 V
Performance		AC input frequency	50 - 60 Hz
NVIDIA G-SYNC *	✗	Operational conditions	
AMD FreeSync *	✓	Operating temperature (T-T)	0 - 40 °C
Flicker-free technology	✓	Operating relative humidity (H-H)	20 - 90%
Low Blue Light technology	✓	Packaging content	
Multimedia		Cables included	Audio (3.5mm), DisplayPort, HDMI, USB
Built-in speaker(s) *	✓	Weight & dimensions	
Built-in camera *	✗	Width (with stand)	809 mm
Number of speakers	2	Depth (with stand)	299 mm
RMS rated power	10 W	Height (with stand)	610 mm
Design		Weight (with stand)	12,1 kg
Market positioning *	Graphics design	Width (without stand)	809 mm
Product colour *	Black	Depth (without stand)	105 mm
Frameless design	✓	Height (without stand)	366 mm
Front bezel colour	Black	Weight (without stand)	7,4 kg
Detachable stand	✓	Packaging data	
Feet colour	Black	Package width	965 mm
Country of origin	China	Package depth	590 mm
Certification	CB, CE, CE EMC, WEEE, RoHS, ErP, REACH, UkrSEPRO cTUVus, FCC-B, ICE, Mexico CoC, EPEAT, Energy Star, Mexico Energy CCC, CEL, China RoHS	Package height	370 mm
		Package weight	17,2 kg
Ports & interfaces		Logistics data	
Built-in USB hub *	✓	Harmonized System (HS) code	85285210
USB hub version	3.2 Gen 1 (3.1 Gen 1)		
Number of USB Type-B upstream ports quantity	1		
USB Type-A downstream ports quantity	2		
USB Type-C downstream ports quantity	1		
DVI port	✗		



0766907002287



766907002287

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.