Viewsonic X11-4KP data projector Standard throw projector LED 4K (4096x2400) 3D Black, Brown

Brand : Viewsonic Product code: X11-4KP

Product name: X11-4KP

- True 4K HDR immersive visual experience
- Cinema SuperColor+ $\ensuremath{^{\text{\tiny TM}}}$ Technology with 125% Rec.709 wide color gamut
- 3rd generation LED technology with 30,000 hours lifespan
- Smart connectivity via Wi-Fi, Bluetooth, and USB-C
- Custom-built speakers by Harman Kardon
- Instant auto focus and 0.8 short throw ratio for easy setup

 3840×2160 , 2400 LED Lumens, 1.07G, LED, 15GB, 15K - 135KHz, 23 - 120 HZ, 2x HDMI, 1x Type-C, 3.5mm, RJ-45, WIFI input, Audio-out Bluetooth, S/PDIF x1

Viewsonic X11-4KP. Projection technology: LED, Projector native resolution: 4K (4096x2400), Contrast ratio (typical): 3000000:1. Light source type: LED, Service life of light source: 30000 h. Aperture range (F-F): 1,8 - 8,5, Offset: 100%. Serial interface type: RJ-45, HDMI connector type: Full-size. Compatible memory cards: MicroSD (TransFlash), Internal storage capacity: 16 GB







Projector		Features	
Projector brightness Screen size compatibility * Projection distance Projection technology * Projector native resolution *	2400 LED lumens 762 - 5080 mm (30 - 200") 0,5 - 3,5 m LED 4K (4096x2400)	Noise level (economic mode) On Screen Display (OSD) Number of OSD languages Noise level *	25 dB ✓ 24 26 dB
		Multimedia	
Contrast ratio (typical) * Native aspect ratio * Keystone correction, horizontal Keystone correction, vertical	3000000:1 16:9 40° 40°	Built-in speaker(s) * RMS rated power Number of built-in speakers	√ 16 W 2
Light source		Design	
Light source type * Service life of light source * Lens system	LED 30000 h	Market positioning * Product type * Product colour * LED indicators	Home cinema Standard throw projector Black, Brown
Aperture range (F-F)	1,8 - 8,5	Display	•
Zoom capability	✓	Built-in display *	×
Offset	100%	Power	
Video		Power source *	AC
Full HD * 3D *	√	Power consumption (typical) *	115 W
	V	Power consumption (standby) *	0,5 W
Ports & interfaces	E II .	AC input voltage	100-240 V
HDMI connector type HDMI version	Full-size 2.0	AC input frequency	50-60 Hz
USB 2.0 ports quantity *	2	Operational conditions	
USB 3.2 Gen 1 (3.1 Gen 1) Type-C	1	Operating temperature (T-T)	0 - 40 °C
ports quantity	_	Weight & dimensions	
Serial interface type * HDMI ports quantity *	RJ-45 2	Width	261 mm
Network	-	Depth Height	271 mm 146 mm
Ethernet LAN *	1	Weight *	4,5 kg
Ethernet LAN (RJ-45) ports	√ 1	Package width	402 mm
Wi-Fi *	·	Package depth	370 mm
Storage		Package height	295 mm
Card reader integrated *	√	Package weight	7,5 kg
Compatible memory cards	MicroSD (TransFlash)	Packaging content	
Internal storage capacity	16 GB	Remote control included * Remote control type	√ IR

Packaging content		
Cables included	Power, USB Type-C	
Logistics data		
Quantity per pack	1 pc(s)	

